

Manipulators, Goniometers and Mechanical Feedthroughs

Multi Axes Manipulator Information List

Z TRAVEL

- 0 mm (XY only)
 75 mm
 100 mm
 125 mm
 150 mm
 175 mm
 200 mm
 225 mm
 250 mm
 275 mm
 300 mm
 325 mm
 350 mm
 375 mm
 400 mm
 425 mm
 450 mm
 475 mm
 500 mm
 525 mm
 550 mm
 575 mm
 600 mm
 625 mm
 650 mm
 675 mm
 700 mm
 725 mm
 750 mm
 775 mm
 800 mm
 Other mm

MOUNTING FLANGE

- DN 100CF
 DN 160CF
 Other DN CF

TRAVELING FLANGE

- DN 100CF
 DN 160CF
 Other DN CF

MOUNTING ATTITUDE

- Vertical
 Horizontal
 Other

XY TRAVEL

- 0 mm (Z only)
 ±12.5 mm
 Other mm

HEATING

- to °C

ROTATION

- R1
 R2
 R3
 Differentially Pumped Rotary Feedthrough

COOLING

- to °C

MOTORIZATION

- X axis
 Y axis
 Z axis
 R1
 R2
 R3

THERMOCOUPLES

- Type K pairs
 Type C pairs
 Type E pairs
 Other type pairs

APPLICATION

Please describe: _____

OTHER REQUIREMENTS

Please describe: _____

